THE BALTIC EXCHANGE DRY CARGO QUESTIONNAIRE (BALTIC99)

1	GENERAL INFORMATION		
1.1	Date updated:	31/1	0/2020
	Vessel's name:		EE NAREE
	IMO number:		51224
1.4	Vessel's previous name(s) and date(s) of change:		V/A
	Flag:		APORE
	Port of Registry:		APORE
	Type of vessel:		CARRIER
	Type of vessel.		NGLE
	and Operation	Oii	VOLE
Ownership	and operation		
1.9	Registered owner - Full style:		IDES PTE. LTD. ET, SINGAPORE (079329)
1.1	Parent company/group to which the owner belongs - Full style:		
1.11	Technical operator - Full style:	Cathay House, 8/35 10th Silom, Bangrak, Ban Tel: (662) 696 8900 to 99 8	IPPING AGENCY LTD. h Floor, North Sathorn Rd. igkok -10500, Thailand o, Fax: (662) 237 7842, 633 468 eciousshipping.com
1.12	Commercial operator - Full style:	PSL Post Fixture Team Cathay House , 8/35 North Sathorn Road Bangkok 10500 Thailand E-Mai : postfix@preciousshipping.com	
1.13	Disponent owner - Full style:	DAMPSKIBSSELSKABET NORDEN A/S 52,Strandvejen DK 2900 Hellarup Denmark , operations@ds-norden.com	
1.14	Does disponent owner have vessel on time charter or bareboat:	ħ	N.A.
1.15	Since when vessel has been under Disponent owner:	ı	N.A.
	Number of vessels in disponent owner's fleet:	ı	V.A.
Builder	'		
1.17	Builder (where built) / Yard number:	TAIZHOU SANFU SHIPYARD, CHINA	SF130128
	Date delivered (built):	21/0	4/2016
Classification			
1.19	Classification society:	NIPPON K	AIJI KYOKAI
1.2	Class notation:	NS* (CSR, BC-A, BC-XII, GRAB [20], PSPC-WBT), (ESP), (IWS), (BWTS), (PSCM), (Strengthened for heavy cargo loading where holds no.2 & 4 may be empty), MNS*(MO)	
1.21	If Classification society changed, name of previous society:		V/A
1.22	If Classification society changed, date of change:	1	V/A
1.23	Date and place of last dry dock:	2-15 JANUARY 2019	SHANHAIGUAN SHIPYARD
1.24	Date next dry dock is due:	Ар	or-21
1.25	Date of last special survey / next survey due:	N/A	Apr-21
1.26	Date of last annual survey / next survey due:	Aug-20	Apr-21
1.27	Is vessel entered in classification approved enhanced survey program?	Υ	'ES
1.28	Does vessel comply with IACS unified requirements regarding number 1 cargo hold and	Y	'ES
	double bottom tank steel structure? Has this compliance been verified by the classification society?		<u>′</u> ES
Dimensions			
	Length Over All (LOA):	100	0.90 M
	Length Between Perpendiculars (LBP):		
1.3	zongm zomoon i dipondidatio (EDI).	194.5 M	

1.31	Extreme bre	eadth (Beam):				32	.26 M
1.32	Moulded de	epth:			18.50 M		
1.33	Keel to Mas	sthead (KTM) / KTM in collapsed condit	ion (if applical	ble):		48.	633 M
1.34	or	om waterline to top of hatch coamings		No1. Hatch	Mids	nips	Last Hatch
	Ballast con			16.32	15.	01	14.01
	Full ballast	condition: ds flooded, basis 50% bunkers)		13.34	12	43	11.82
	Fully laden	,		7.95	7.6	55	7.64
1.35		om keel to top of hatch coamings (or covers if side-rolling hatches):		21.109 M	20.80	0 M	20.803 M
onnages							
1.36	Gross Tonn	age (GT) / Net Registered Tonnage (N	RT):		364	16	21225
1.37	Suez Canal	Tonnage – Gross (SCGT) / Net (SCNT	Γ):		3699	2.78	32344.12
1.38	Panama Ca	anal Net Tonnage (PCNT):				3	0147
oadline Inf	formation						
1.39	Loadline			Deadweight	Dra	aft	TPC
	Summer:			63016.24	13.3	300	62.2
	Winter:			61293.84	13.0	23	62.1
	Winter Nort	h Atlantic:		61293.84	13.0	23	62.1
	Fresh water	r:		63016.24	13.6	602	62.3
	Tropical:			64740.34	13.5	77	62.3
	Tropical fre	sh water:		64740.34	13.8	79	62.3
	Full Ballast condition: (ballast holds not flooded, basis 50% bunkers) (abo		bout)	18785.69	5.910		55.900
	Lightship: Draft: F- 0.471 M/ A- 4.749 M Displacement: 12069.56 mt			2.6	10	52.700	
	•	FWA at summer draft:			2.0		2 MM
	TPC on sur						52.2
vessel fitt							, <u>.</u>
		anama Canal?				\	YES
		deadweight all told on 39ft 6in / 12.039	m (SG 0 995	4).			5.840 MT
		nama deadweight all told affected by ve			NO		
	Transit of S		cooci o blige t	um radius:			/ES
		t. Lawrence Seaway?					N/A
		deadweight all told on 26ft / 7.92m fres	sh water:				N/A
ecent Ope	rational His	story					
					Pollution:		NO
1.43	Has vessel	been involved in a pollution, grounding	, serious casu	alty or collision incident	Grounding:		NO
	during the p	past 12 months? If yes, give details:			Casualty:		NO NO
					Collision:		NO NO
1.44	Voyage His Voy#	Charterer Charterer		Cargo		l oad-Die	charge Ports
	Last:	DS-NORDEN (PERIOD T/C) ,DHL PROJECT (SUB-CHTRS)	BRAZILIAN	RAW SUGAR IN BULK	SANTOS,BRA		AGONG, BANGLADESH
	2 nd :	DS-NORDEN (PERIOD T/C) ,AGROCORP INT'L (SUB-CHTRS)	WHEAT IN I	BULK	YUZHNYY,UF INDONESIA	CRAINE - JAK	KARTA,SURABAYA-
	3 rd :	DS-NORDEN (PERIOD T/C)	BAUXITE IN	BULK		JINEA - DNE	PROBUGSKY,UKRAINE
	4 th : DS-NORDEN (PERIOD T/C) GYPSUM IN BULK GARRUCHA,SPAIN - LAGOS-CALAB.		OS-CALABAR NIGERIA				
	4 th :	DS-NORDEN (PERIOD T/C)	GYPSUM IN	BULK	drift(to cirri,c	ATTIN ETIG	
	4 th : 5 th :	DS-NORDEN (PERIOD T/C) ACCELORMITTAL (VOYAGE)	COAL IN BU		NORFOLK, U		<u> </u>

2	CERTIFICATION	Issued	Last Annual	Expires
2.1	Safety Equipment Certificate:	16/08/2020	16/08/2020	20/04/2021
2.2	Safety Radio Certificate:	16/08/2020	16/08/2020	20/04/2021
2.3	Safety Construction Certificate:	16/08/2020	16/08/2020	20/04/2021
2.4	Loadline Certificate:	16/08/2020	16/08/2020	20/04/2021
2.5	Safety Management Certificate (SMC):	14/10/2016	17/07/2019	25/08/2021

2.6	Document of Compliance (DOC):	30/10/2015	13/11/2019	19/11/2020
2.7	Cargo Gear survey:	21/04/2016	16/08/2020	20/04/2021
	Cargo securing manual:	30/12/2015	N/A	N/A
2.9	International Oil Pollution Prevention Certificate (IOPPC):	10/11/2017	16/08/2020	11/07/2022
	Ship Sanitation Control (SSCC) / Ship Sanitation Control Exemption (SSCE) Certificate	27/05/2020	N/A	27/11/2020
2.11	USCG COFR:	30/03/2019	N/A	30/03/2022
2.12	International Ship Security Certificate (ISSC):	14/10/2016	18/07/2019	25/08/2021

3 CREW MANAGEMENT	
3.1 Number of Officers: (including N	Master) 11
3.2 Number of crew:	10
3.3 Name and nationality of Master:	CAPT. VISAROJ SIRISAKULVEROJ/THAI
3.4 Nationality of Officers:	Thai / Indian
3.5 Nationality of crew:	Thai / Indian
3.6 What is the common working la	nguage onboard: ENGLISH
3.7 Do officers speak and understar	nd English?

4	SAFETY MANAGEMENT		
4.1	Is the vessel ISM certified?	YE	S
4.2	Document of Compliance (DOC) certificate number / issuing authority:	15HO-2094SGPDOC NKK	
4.3	Safety Management (SMC) certificate number / issuing authority:	ST-16HO-1785SMC	NKK
	State outstanding recommendations, if any:	NI	IL
4.4	Is the vessel operated under a Quality Management System?	YES	
	If Yes, what type of system (ISO9002 or IMO Resolution A.741(18)):	IMO RESOLUT	TON A.741(18)

5	CARGO ARRANGEMENTS		
Holds			
5.1	Number of holds:	5	
5.2	Hold dimensions: L x B x H	HOLD 1: 29.52 x (F 14.69 A 23.824) x 19.32 HOLD 2: 33.62 x 23.824 x 19.32 M HOLD 3: 31.16 x 23.824 x 19.02 M HOLD 4: 31.16 x 23.824 x 19.02 M HOLD 5: 29.52 x (F 23.824 A 8.966) x 19.02	
5.3	Are vessel's holds clear and free of any obstructions?	YES	
5.4	Capacity, by hold, excluding wing/topside tanks but including hatchways:	Grain	Bale
	Hold #1:	13984.51	13200
	Hold #2:	17717.88	16650
	Hold #3:	15381.23	14080
	Hold #4:	15882.18	15000
	Hold #5:	14974.74	14500
	Total:	77940.54	73430
5.5	Is vessel strengthened for the carriage of heavy cargoes?	YES	
5.6	If yes, state which holds may be left empty:	2 & 4	
5.7	Is tanktop steel suitable for grab discharge?	YES	
5.8	State whether bulkhead corrugations are vertical or horizontal:	VERTICAL	
	Tanktop strength:	HOLDS 1, 3 & 5 – 25T/M2 , HOLDS 2 &	4 – 20T/M2
5.1	Are holds CO2 fitted?	YES	
5.11	Are holds fitted with smoke detection system?	YES	
5.12	Is vessel fitted with Australian type approved holds ladders?	YES	
5.13	Has vessel a functioning class certified loadmaster/loadicator or similar calculator?	YES	
5.14	Are holds hoppered at:		
	Forward bulkhead?	YES HOLD	3
	Aft bulkhead?	YES HOLDS 1	,3,4
5.15	·	NO	
5.16	Measurement of any tank slopes/hoppering: (height and distance from vessel's side at tank top)	HOLD 1: H 4.22~5.90M x D 4.22~8.22M; HOLD 2: H 4.22M x D4.22M HOLD 3: H 4.22M x D 4.22M HOLD 4: H 4.22M x D 4.22M HOLD 5: H 4.22~9.06M x D 4.22~11.65M	

when loading a full cargo (deadweight) of heavy grain in bulk (stowage factor 42 cu. Feet) with ends untrimmed? 5.21 Is the vessel fitted with A60 Steel Bulkhead? Feet and Hatches 5.22 Number of hatches: 5.23 Make and type of hatch covers: McGREGOR, ELECTRO-HYDRAULIC, FOLDING TYPE 5.24 Hatch dimensions: (Length X Breadth) 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 5.26 Strength of hatch covers: HOLD 1: 5.1–6.8 TM2 HOLD 2: 3.4 8 6: 3.5 TM2 5.27 Number, diameter and location of cement holes 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1 st hold opening: 5.30 Distance from bow to fore of 1 st hold opening: 5.31 State deck strength: Ballast 5.32 Capacity of ballast tanks (100%): 10 M³ YES YES YES YES NCREGOR, ELECTRO-HYDRAULIC, FOLDING TYPE McGREGOR,	5.18	Flat floor measurement of cargo holds at tank top: L x W HOLD 1: 27.06 x 14.69-23.824 M HOLD 2: 33.62 x 23.824 M HOLD 3: 26.24 x 23.824 M HOLD 4: 28.70 x 23.824 M HOLD 4: 28.70 x 23.824 M HOLD 5: 29.52 x 8.966-23.824 M HOLD 5: 29.52 x 8.966-23.824 M 5.18 Are vessel's holds electrically ventilated? NO If yes, state number of air-changes per hour basis empty holds: N/A Type of hold paint: CURED EPOXY Is vessel fitted for carriage of grain in accordance with chapter V1 of SOLAS 1974 and amendments without requiring bagging, strapping and securing 1974 and amendments without requiring bagging, strapping and securing 1974 and amendments without requiring bagging, strapping and securing 1975 years 1976 and 1976 a		62 x 23.824 M 24 x 23.824 M 70 x 23.824 M 52 x 8.966~23.824 M NO N/A	
Deck and Hatches 5.22 Number of hatches: 5.23 Make and type of hatch covers: McGREGOR, ELECTRO-HYDRAULIC, FOLDING TYPE 5.24 Hatch dimensions: (Length X Breadth) 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 148.50 M 5.26 Strength of hatch covers: HOLD 1: 5.1-6.8 T/M2 HOLD 2,3.4 & 5: 3.5 T/M2 5.27 Number, diameter and location of cement holes 2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1st hold opening: 5.29 Distance from stern to aft of last hold opening: 5.30 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 8.33 Ballast holds capacity, state which hold(s): NO 3 HOLD - 15350 M3 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting in the / rat		factor 42 cu. Feet) with ends untrimmed?			
5.22 Number of hatches: 5.23 Make and type of hatch covers: 6.24 Hatch dimensions: (Length X Breadth) 6.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 6.26 Strength of hatch covers: 7.27 Number, diameter and location of cement holes 8.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 8.29 Distance from bow to fore of 1st hold opening: 8.29 Distance from stern to aft of last hold opening: 8.20 Distance from stern to aft of last hold opening: 8.20 Distance from stern to aft of last hold opening: 8.20 Distance from stern to aft of last hold opening: 8.20 Distance from stern to aft of last hold opening: 8.21 Distance from stern to aft of last hold opening: 8.22 Distance from stern to aft of last hold opening: 8.23 Capacity of ballast tanks (100%): 8.24 Distance holds capacity, state which hold(s): 8.25 Capacity of ballast tanks (100%): 8.26 Distance holds capacity, state which hold(s): 8.27 Capacity of ballasting time / rate of ballasting / Vessel's deballasting time / rate of	5.21	Is the vessel fitted with A60 Steel Bulkhead?		YES	
5.23 Make and type of hatch covers: 6.24 Hatch dimensions: (Length X Breadth) 6.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 6.26 Strength of hatch covers: 7.27 Number, diameter and location of cement holes 8.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 6.29 Distance from bow to fore of 1st hold opening: 6.30 Distance from stern to aft of last hold opening: 6.31 State deck strength: 6.32 Capacity of ballast tanks (100%): 6.33 Ballast holds capacity, state which hold(s): 7.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting in the rate of deballasting in the rate of deballasting in the rate of support in the rate of deballasting in the rate of support in t					
5.24 Hatch dimensions: (Length X Breadth) 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 5.26 Strength of hatch covers: 5.27 Number, diameter and location of cement holes 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1st hold opening: 5.30 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting deballasting ime / rate of deballasting ime / rate of deballasting ime / rate of 2x259 deballasting ime	5.22	Number of hatches:		5	
S.24 Hatch dimensions: (Length X Breadth) NO. 2-5: 22.96 M X 18.26 M	5.23	Make and type of hatch covers:		McGREGOR, ELECTRO-HYDRAULIC, FOLDING TYPE	
5.26 Strength of hatch covers: 5.27 Number, diameter and location of cement holes 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1st hold opening: 5.20 Distance from stern to aft of last hold opening: 5.30 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.33 Distance from bow to fore of 1st hold opening: 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of 2x650 M3 per HR	5.24	5,24 Hatch dimensions: (Length X Breadth)			
5.26 Strength of hatch covers: HOLD 2,3,4 & 5: 3.5 T/M2 2 PER HOLD, LOCATED ON FWD AND AFT PONTOON, DIA 860MM 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1 st hold opening: 5.20 Distance from stern to aft of last hold opening: 5.30 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting time / rate of 2x650 M3 per HR / 14HRS / 2x650 M3 per HR	5.25	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):		148.50 M	
5.27 Number, diameter and location of cement noies Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): Ship's rail to near edge of walkway – 4.63m Ship's rail to far edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 3.90m, Hold3 – 3.10m, Hold4 – No clear space, Hold5 – 2.08m 5.29 Distance from bow to fore of 1 st hold opening: 5.30 Distance from stern to aft of last hold opening: 5.31 State deck strength: Not allow to load any cargo on deck. Ballast 5.32 Capacity of ballast tanks (100%): NO.3 HOLD - 15350 M3 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 12.3 HRS / 2x750M3 per HR / 14HRS / 2x650 M3 per HR	5.26	Strength of hatch covers:			
5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1 st hold opening: 5.3 Distance from stern to aft of last hold opening: 5.3 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 5.28 Distance from stern to aft of last hold opening: 5.39 Distance from stern to aft of last hold opening: 5.30 No. allow to load any cargo on deck. 5.31 No. allow to load any cargo on deck. 5.32 Capacity of ballast tanks (100%): 5.33 Distance from stern to aft of last hold opening: 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting	5.27	27 Number, diameter and location of cement holes			
5.3 Distance from stern to aft of last hold opening: 5.31 State deck strength: Not allow to load any cargo on deck. Ballast 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): NO.3 HOLD - 15350 M3 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 12.3 HRS / 2x750M3 per HR / 14HRS / 2x650 M3 per HR	5.28			Ship's rail to far edge of coaming – 7m Clear distance: Hold1 – 1.80m, Hold2 – 3.90m, Hold3 –	
5.31 State deck strength: Ballast 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting 12.3 HRS / 2x750M3 per HR / 14HRS / 2x650 M3 per HR	5.29	Distance from bow to fore of 1 st hold opening:		16.20 M	
Ballast 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): NO.3 HOLD - 15350 M3 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 12.3 HRS / 2x750M3 per HR / 14HRS / 2x650 M3 per HR	5.3	Distance from stern to aft of last hold opening:		35.20 M	
5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): NO.3 HOLD - 15350 M3 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 12.3 HRS / 2x750M3 per HR / 14HRS / 2x650 M3 per HR	5.31	State deck strength:		Not allow to load any cargo on deck.	
5.33 Ballast holds capacity, state which hold(s): NO.3 HOLD - 15350 M3 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 12.3 HRS / 2x750M3 per HR / 14HRS / 2x650 M3 per HR	Ballast				
5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting time / rate of 2x650 M3 per HR / 14HRS / 2x650 M3 per HR	5.32	Capacity of ballast tanks (100%):		18399.45 M3	
5.35 deballasting 2x650 M3 per HR	5.33	Ballast holds capacity, state which hold(s):		NO.3 HOLD - 15350 M3	
5.36 Unpumpable quantity: 100 M ³	5.34 5.35	Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting	of		
	5.36	Unpumpable quantity:		100 M ³	

6	CARGO GEAR (ONLY TO BE COMPLETED IF APPLICABLE)		
6.1	If geared state make and type:	MASADA-MITSUBISHI, EI	CRANES. LECTRO-HYDRAULIC, SWL 8MT WITH GRAB
6.2	Number/location of derricks-/ cranes:	4 NOS. / BETWEEN HOLD	S 1&2, 2&3, 3&4, 4&5
6.3	Maximum outreach of gear beyond ships rail	13.	87 M
6.4	Maximum outreach of gear beyond ships rail with maximum cargo lift on hook:	13.	87 M
6.5	If gantry cranes/horizontal slewing cranes - state minimum clearance distance crane hook to top of hatch coaming:	1	N/A
6.6	Time needed for full cycle with maximum cargo lift on hook:	12	0 sec
6.7	Hoisting time of gear: (Load / Metres Minutes) Hook Grab	LOAD 367/142/5 KN – SPEED 22/44/55 m/min	
6.8	Luffing time of gear:	58sec / FROM 20° TO 80°	
6.9	Slewing time of gear:	0.45 RPM	
6.1	Is gear combinable for heavy lift?	N/A	
6.11	Are winches electro-hydraulic?	YES	
6.12	If vessel has grabs on board - state:	YES, 4 NOS	
	Туре:	TOBU-ELECT	RO/HYDRAULIC
	Weight:	9	MT
	Lifting Capacity:	6/1	2M3
	Power source of grabs:	440/110V, 60HZ	3-AC
	Location of power source:	INSIDE CI	RANE POST
6.13	Does vessel have enough power to run 4 cranes and 4 shore grabs (if applicable). If not pls state how many?	YES	
6.14	Is vessel fitted with sufficient lights at each hatch for night work?	YES, PORT	ABLE LIGHTS
6.15	Is vessel logs fitted?	NO	

6.16	Is vessel log racks fitted?			N/A
	Timber Loadline (if applicable)	Deadweight	Draft	TPC
0.17	Summer:	2 Gadin orgin	2.3	
	Winter:			
	Winter North Atlantic:			
			21/2	
	Fresh water:		N/A	
	Tropical:			
	Tropical fresh water:			
7	,			
7.1	Capacity in direct stow of TEU/FEU basis empty to	nks:		
	Capacity in direct stow of TEU/FEU basis full tanks	S:		
7.2	Are all containers within reach of vessel's gear?			
7.3	If no, state self sustained capacity:			
	If vessel fitted with all permanent and loose fittings	s/lashing materials for above number of		
7.4	TEU/FEU?	-		
7.5	Is vessel fitted with recessed holes/shoes on tank	op and container shoes on		
	weatherdeck and hatch covers?	- dl TEU.		
/.6	Advise stack weights and number of tiers on/unde			
	Advise stack weights and number of tiers on/unde	r deck per FEU:		
	Has vessel a container spreader on board?			
7.8	Number and type of reefer plugs:			
8	ENGINE ROOM, SPEED AND CONSUMPTION			
8.1	Is vessel fitted with a shaft generator?			NO
Engine Roo	om			
8.2	Engine make/model and type:		MAN-B&W 5G	60ME-C9.2(Tier II)
8.3	BHP / RPM of main engine at MCR:	100%	11398.7 BHP	77.0 RPM
0.4	BHP / RPM of main engine at NCR (as % of	770/	004F 4 DUD	70.0 DDM
8.4	MCR):	77%	8845.4 BHP	70.8 RPM
8.5	GENERATORS :		ANQING CSSC	, 6DK-20e, 3x700kW
Fuel				
8.5	What type/viscosity of fuel is used for main propul			017 VLSFO (Sulphur< 0.5%) 3217:2017 LSMGO (Sulphur <
	Capacity (100%) of main engine bunker tanks (LS unpumpables):	IFO + HSIFO; excluding	710 CBM.	1430 CBM.
8.6	What type/viscosity of fuel is used in the generating	g plant:	RMG 380CST ISO 8217:2017 VLSFO (Sulphur< 0.5%) + In ECA area, DMA ISO 8217:2017 LSMGO (Sulphur < 0.1%)	
	Capacity (100%) of aux engine(s) bunker tanks (Lunpumpables):	SMGO + HSMGO; excluding	INCLUDED IN M/E TANKS	
Speed	I			
8.7	Ballast:	ABT	AS PER VESS	EL DESCRIPTION
	Laden:	ABT		
Consumpti	ons			
8.8	Passage		Main	Aux
	Ballast:	ABT		
	Laden:	ABT		
8.9	In Port			
	Working:		AS PER VESS	EL DESCRIPTION
	ldle:			
	Other (specify):			
9	MISCELLANEOUS			
Communica	ations and Electronics			
9.1	Call sign:		9\	/3873
	Vessel's INMARSAT – C number:			2, 456390713
			.0000011	
0.2	Vessel's telephone number:	+ 870	773211375	
	Vessel's telephone number:		+ 870 7	773211375
9.4	Vessel's fax number:			-
9.4 9.5	Vessel's fax number: Vessel's email address:		<u>vessel@preci</u>	- ousshipping.com
9.4 9.5 9.6	Vessel's fax number:	Identity Code):	vessel@preci 563	-

9.7 Vessel's onboard electrical supply (V / Hz):

220V / 60Hz

Constants/	Fresh Water		
9.8	Constants excluding fresh water:	525 MT	
9.9	Daily freshwater consumption:	10 MT	
9.1	Fresh water capacity:	301 MT	
9.11	State daily production of evaporator:	18 MT/DAY	
9.12	Normal fresh water reserve:	200 MT	
Insurance			
9.13	P & I Club - Full style:	UK P&I Club, Thomas Miller P&I (Europe) Ltd. Address: 90 Fenchurch Street, London EC3M 4ST	
9.14	P & I Club coverage (US \$):	AS PER P&I RULES	
9.15	Where is the owners hull and machinery placed:	Sveriges Angfartygs Assurans Forening The Swedish Club	
9.16	Hull & Machinery insured value (US \$):	AS PER VESSEL DESCRIPTION	
Vetting			
9.17	Is the vessel RIGHTSHIP approved:	N/A (NEW VESSEL)	
9.18	Date/Place of last RIGHTSHIP Inspection:	N/A	
Port State (Control		
9.19	Date and place of last Port State Control inspection:	27 MAY 2020 AT DNEPROBUGSKY, UKRAINE	
9.2	Has the vessel been detained by Port State Control in the last 12 months?	NO	
	Any outstanding deficiencies as reported by any Port State Control. If yes, provide details:	NO	
9.21	Any Australian Maritime Safety Authority (AMSA) detentions or noted deficiencies. If so, please advise details and specify when/where these items were repaired.	NO	

10	SUPF	PLEMENTARY INFORMATION FOR SPECIFIC COMMODITIES/TRADES
10.1		NONE

2008 (BalticExchange.com / Baltic99.com)