THE BALTIC EXCHANGE DRY CARGO QUESTIONNAIRE (BALTIC99)

1	GENERAL INFORMATION		
1.1	Date updated:	31-Dec-23	
1.2	Vessel's name:	M.V.WARI	SA NAREE
1.3	IMO number:	934	3417
1.4	Vessel's previous name(s) and date(s) of change:	M.V.GOOD PRIE	DE , 4th SEP 2013
1.5	Flag:	THAI	LAND
1.6	Port of Registry:	BANG	GKOK
1.7	Type of vessel:	BULK C	ARRIER
1.8	Type of hull:	DOUBL	E HULL
Ownership a	and Operation		
1.9	Registered owner - Full style:	Precious Ponds Limited. 8/27-28, 7th Floor, Cathay House, North Sathorn Road, Silom, Bangrak, Bangkok, 10500 Thailand Email: psl@preciousshipping.com	
1.1	Parent company/group to which the owner belongs - Full style:	PRECIOUS SHIPPING PCI 8/27-28, 8th Floor, Cathay I- North Sathorn Road, Silom, Thailand	łouse,
1.11	Technical operator - Full style:	Great Circle Shipping Agency Limited. 8/35 North Sathorn Road, Bangkok, Thailand 10500, Tel: +66 2 696 8900 up tp 8999, Fax +66 2 237 7842, Email: gcship@preciousshipping.com	
1.12	Commercial operator - Full style:	PRECIOUS SHIPPING PCL , BANGKOK 8/27-28, 8th Floor, Cathay House, North Sathorn Road, Silom, Bangrak, Bangkok, 10500 Thailand. Email: gcship@preciousshipping.com	
1.13	Disponent owner - Full style:	LOUIS DREYFUS COMPANY SUISSE S.A. GVA Centre, 29 route de l'Aéroport – P.O. Box 236, 1215 Geneva, Switzerland Martin Viquesnel Vessel Operator Phone: +41 (0)58 688 25 93 Mobile: +41 (0)79 388 04 24 Email: martin.viquesnel@ldc.com	
1.14	Does disponent owner have vessel on time charter or bareboat:	TIME C	HARTER
1.15	Since when vessel has been under Disponent owner:	21-N	ov-23
1.16	Number of vessels in disponent owner's fleet:	N	.A.
Builder		•	
1.17	Builder (where built) / Yard number:	Hindustan Shipyard Limited	11136
1.18	Date delivered (built):	12-A	pr-10
Classification	n		
	Classification society:		AIJI KYOKAI
	Class notation:	NS(BC-A,BC-XII)(ESP)(IWS)(IHM)/MNS.	
	If Classification society changed, name of previous society:	Lloyd's register	
	If Classification society changed, date of change:	16/04/2023	
_	Date and place of last dry dock:	16-Apr-23 shanhaiguan shipyard	
	Date next dry dock is due:	16-Jul-25	
_	Date of last special survey / next survey due:	16-Jul-20	16-Jul-25
	Date of last annual survey / next survey due:	16-Apr-23 15-Apr-24 YES	
1.27	Is vessel entered in classification approved enhanced survey program? Does vessel comply with IACS unified requirements regarding number 1 cargo hold and	Y	E0
1.28	double bottom tank steel structure? Has this compliance been verified by the classification society?	YES YES	
Dimensions			
	Length Over All (LOA):	100	00 M
_	Length Between Perpendiculars (LBP):	190.00 M 183.25 M	
	Extreme breadth (Beam):	183.25 M 32.26 M	
	Moulded depth:	32.26 M 17.50 M	
	Keel to Masthead (KTM) / KTM in collapsed condition (if applicable):	17.50 M 45.58 M / N.A.	
1.33	Distance from waterline to top of hatch coamings or	45.561	,
1.34	Distance from waterline to top of natch coamings of No1. Hatch	Midships	Last Hatch

1.45	Specify the s	security level at which the ship is curre	ently operating (ISSC):	MAI	RSEC LEVEL: ONE
	5 th :	DAEWOO LOGISTICS CORP.		EEL PRODUCTS	ALTAMIRA, M	G- POHANG -VIA PANAMA- MEXICO-HOUSTON, USA
	4 th :	XO SHIPPING A/S	PE ⁻	TCOKE IN BULK	BEAUMONT	-VIA PANAMA-KANDA
	3 rd :	K - LINE	STE	EEL PRODUCTS		PUERTO CALDERA, BARRANQUILLA
	2 nd :	JERA GLOBAL MARKETS PTE LTD	STEA	AM COAL IN BULK	PUERTO DRI	UMMOND - GDANSK
	Last:	LOUIS DREYFUS COMPANY SUISSE S.A.	W	HEAT IN BULK	RIGA - MOM	BASA
	Voy#	Charterer		Cargo	Load-Dischar	ge Ports
1.44	Voyage Histo	ory				
1.43	Has vessel b	neen involved in a pollution, grounding ast 12 months? If yes, give details:	g, serious casua	alty or collision incident	Pollution: N/A Grounding: N/A Casualty: N/A Collision: N/A	
Recent Ope	rational Hist	ory				
		deadweight all told on 26ft / 7.92m fre	esh water:			-
		Lawrence Seaway?				NO
1.41	Transit of Su		~			res
	-	ama deadweight all told affected by v				NO
1.4		deadweight all told on 39ft 6in / 12.03	9m (SG 0 9954).		163 mt
Is vessel fit		ınama Canal?				/ES
le vecesi fit	TPC on sum	mer draft				57.3
	FWA at sum					4 mm
	Lightship: Dr	•	mt		2.69	11244.9
	`	s not flooded, basis 50% bunkers) (a		11029		
	Full Ballast c			17529	6.06	51.7
	Tropical fres	h water:		55318	13.17	57.5
	Tropical:			55348	12.886	57.4
	Fresh water:			53842	12.907	57.5
	Winter North	Atlantic:		-	-	-
	Winter:			52334	12.36	57.2
1.39	Summer:			53839	12.623	57.3
	Loadline			Deadweight	Draft	TPC
1.38 Loadline Inf		nal Net Tonnage (PCNT):			2	7078
		Tonnage – Gross (SCGT) / Net (SCN	vi):		33174.86	29805.4
	!	age (GT) / Net Registered Tonnage (N			32661	18210
Tonnages	of natch cove	ers ii side-rolling natches).				
1.35		oridition: n keel to top of hatch coamings (or toers if side-rolling hatches):	ор	7.27 M 20.8 M	7.27 M 20.35 M	7.27 M 19.90 M
	ì	s flooded, basis 50% bunkers)		7.27 M	7 27 M	7 27 M
	Full ballast c			11.79 M	11.09 M	10.38 M
		s not flooded, basis 50% bunkers)		14.91 M	13.62 M	12.32 M
	Ballast condi	ition:				

2 CE	ERTIFICATION	Issued	Last Annual	Expires
2.1 Sa	afety Equipment Certificate:	01-Jun-23	16-Apr-23	11-Apr-25
2.2 Sa	afety Radio Certificate:	01-Jun-23	16-Apr-23	11-Apr-25
2.3 Sa	afety Construction Certificate:	16-Aug-23	16-Apr-23	11-Apr-25
	adline Certificate:	01-Jun-23	16-Apr-23	11-Apr-25
2.5 (SI	afety Management Certificate MC):	15-Aug-23	-	22-Aug-28
2.6 D1	ocument of Compliance (DOC): 87155-071221F-MLT	04-Nov-20	09-Oct-23	19-Nov-25
2.7 Ca	argo Gear survey:	16-Apr-23	16-Apr-23	15-Apr-28
2.8 Ca	argo securing manual:	31-Aug-11	N/A	N/A
2.9 Int Ce	ternational Oil Pollution Prevention ertificate (IOPPC):	01-Jun-23	16-Apr-23	11-Apr-25

2.1	Ship Sanitation Control (SSCC) / Ship Sanitation Control Exemption (SSCE) Certificate		-	17-Apr-24
2.11	USCG COFR:	31-Jan-22	-	31-Jan-25
2.12	International Ship Security Certificate (ISSC):	15-Aug-23	-	22-Aug-28

3	CREW MANAGEMENT				
3.1	Number of Officers: (including Master)	12 PERSONS			
3.2	Number of crew:	13 PERSONS			
3.3	Name and nationality of Master:	CAPT. PAKORN UENGRATANAKORN			
3.4	Nationality of Officers:	THAI			
3.5	Nationality of crew:	THAI			
3.6	What is the common working language onboard:	ENGLISH			
3.7	Do officers speak and understand English?	YES			

4	SAFETY MANAGEMENT		
4.1	1 Is the vessel ISM certified?		
4.2	Document of Compliance (DOC) certificate number / issuing authority:	20TB-M0076THADOC	NKK
4.3	Safety Management (SMC) certificate number / issuing authority:	23FK-M011600SMC	NKK
	State outstanding recommendations, if any:	N/A	
4.4	Is the vessel operated under a Quality Management System?	YES	
	If Yes, what type of system (ISO9002 or IMO Resolution A.741(18)):		

5	CARGO ARRANGEMENTS		
Holds			
5.1	Number of holds:	5 HOLDS	
5.2	Hold dimensions: L x B x H	NO.1# L :29.6 m x B :(fwd : 8.8 m , aft : 25.6 m) x H : 17.775 m. NO.2# L :26.4 m x B :(fwd : 25.6 m , aft : 25.6 m) x H : 18.075m. NO.3# L :26.4 m x B :(fwd : 25.6 m , aft : 25.6 m) x H : 18.075m. NO.4# L :26.4 m x B :(fwd : 25.6 m , aft : 25.6 m) x H : 18.075m. NO.5# L :29.6 m x B :(fwd : 25.6 m , aft : 7.2 m) x H : 18.075m.	
5.3	Are vessel's holds clear and free of any obstructions?	YES	
5.4	Capacity, by hold, excluding wing/topside tanks but including hatchways:	Grain	Bale
	Hold #1:	12437.90 CBM	12265.00 CBM
	Hold #2:	13395.30 CBM	13136.00 CBM
	Hold #3:	13396.90 CBM	13138.00 CBM
	Hold #4:	13395.20 CBM	13136.00 CBM
	Hold #5:	13319.70 CBM	13147.00 CBM
	Total:	65945.00 CBM	64822.00 CBM
5.5	Is vessel strengthened for the carriage of heavy cargoes?	YES	
5.6	If yes, state which holds may be left empty:	Hold 2 and 4 or Hold 3 hold may be left empty with cargo in other holds of maximum density 1.35 t/m ³	
5.7	Is tanktop steel suitable for grab discharge?	YES	
5.8	State whether bulkhead corrugations are vertical or horizontal:	Vertical Corrugation at fwd and aft bulkheads.	
5.9	Tanktop strength:	25 mt/m² and steel coils (2 tier 25MT each) with 3 layers of dunnage	
5.1	Are holds CO2 fitted?	YES	
5.11	Are holds fitted with smoke detection system?	YES	
5.12	Is vessel fitted with Australian type approved holds ladders?	Yes, Spiral lado	der.
5.13	Has vessel a functioning class certified loadmaster/loadicator or similar calculator?	Yes	
5.14	Are holds hoppered at:		
	Forward bulkhead?	VERTICAL.	
	Aft bulkhead?	d? VERTICAL .	
5.15	Can vessel's holds be described as box shaped?	NO	
5.16	Measurement of any tank slopes/hoppering:	H: 3.75m. / D: 2.0m.	
00	(height and distance from vessel's side at tank top)		
5.17	Flat floor measurement of cargo holds at tank top: L x W	1# L 29.6 m x W (fwd 8.8 m, aft 25.6 m) 2,3,4# L 26.4 m x W (fwd 25.6 m, aft 25.6 m) 5# L 29.6 m x W (fwd 25.6 m, aft 7.2 m)	
5.18	Are vessel's holds electrically ventilated?	NO	
	If yes, state number of air-changes per hour basis empty holds:	N/A	
5.19	Type of hold paint:	JOTUN ,JOTAGUA	RD 630

1# 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 135.20 m 5.26 Strength of hatch covers: 2.5 mt/m² 5.27 Number, diameter and location of cement holes 4holes / 2x fwd and 2x aft, Diam. size : 600 mm 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1st hold opening: 5.3 Distance from stern to aft of last hold opening: 5.3 State deck strength: 4.5 mt/sqm 8allast 5.32 Capacity of ballast tanks (100%): 18,114.70 m3 5.33 Ballast holds capacity, state which hold(s): 13396.9 m3 (No. 3 Hold) Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting	5.2	Is vessel fitted for carriage of grain in accordance with chapter V1 of SOLAS 1974 and amendments without requiring bagging, strapping and securing when loading a full cargo (deadweight) of heavy grain in bulk (stowage factor 42 cu. Feet) with ends untrimmed?	YES	
5.22 Number of hatches: 5.23 Make and type of hatch covers: Electro-hydraulic folding type, TTS Transfolding 5.24 Hatch dimensions: (Length X Breadth) 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 5.26 Strength of hatch covers: 5.27 Number, diameter and location of cement holes 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from stern to aft of last hold opening: 5.30 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.34 Sallast holds capacity, state which hold(s): 5.35 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.21	Is the vessel fitted with A60 Steel Bulkhead?	YES	
5.23 Make and type of hatch covers: Electro-hydraulic folding type, TTS Transfolding 5.24 Hatch dimensions: (Length X Breadth) 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 5.26 Strength of hatch covers: 5.27 Number, diameter and location of cement holes 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from stern to aft of last hold opening: 5.30 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 22.40 m 1 # 19.20 m x 20.80 m 2,3,4,5# 21.60 m x 2	Deck and Ha	atches		
5.24 Hatch dimensions: (Length X Breadth) 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 5.26 Strength of hatch covers: 5.27 Number, diameter and location of cement holes 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1st hold opening: 5.3 Distance from stern to aft of last hold opening: 5.3 Distance from stern to aft of last hold opening: 5.3 State deck strength: 5.3 Capacity of ballast tanks (100%): 5.3 Ballast 5.3 Capacity of ballast tanks (100%): 5.3 State deck strength: 5.3 Capacity of ballast tanks (100%): 5.3 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.22	Number of hatches:	5 Hatches	
5.24 Hatch dimensions: (Length X Breadth) 5.25 Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5): 5.26 Strength of hatch covers: 5.27 Number, diameter and location of cement holes 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1st hold opening: 5.3 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.23	Make and type of hatch covers:	Electro-hydraulic folding type, TTS Transfolding maker.	
5.26 Strength of hatch covers: 5.27 Number, diameter and location of cement holes 4holes / 2x fwd and 2x aft, Diam. size : 600 mm 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1st hold opening: 5.3 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.24	Hatch dimensions: (Length X Breadth)		
5.27 Number, diameter and location of cement holes 4holes / 2x fwd and 2x aft, Diam. size: 600 mm 5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1 st hold opening: 5.3 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 4holes / 2x fwd and 2x aft, Diam. size: 600 mm NO.1# 5.0 m , NO.2,3,4,5# 4.20 m NO.1# 5.0 m , NO.2,3,4,5# 4.20 m 18.40 m. 18.40 m. 18.41 m. 18.41 m. 19.42 m. 19.45 mt/sqm 19.45 mt/sqm 19.46 m. 19.47 m3 19.48 mt/sqm 19.48	5.25	Hatch span (distance from front of forward hatch#1 to aft of rear hatch#5):	135.20 m	
5.28 Distance from ship's rail to near and far edge of hatch covers/coaming near and far (Please advise the minimum width clear of any obstruction for each hold): 5.29 Distance from bow to fore of 1 st hold opening: 5.3 Distance from stern to aft of last hold opening: 5.31 State deck strength: 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.26	Strength of hatch covers:	2.5 mt/m²	
S.28 (Please advise the minimum width clear of any obstruction for each hold): S.29 Distance from bow to fore of 1st hold opening:	5.27	Number, diameter and location of cement holes	4holes / 2x fwd and 2x aft, Diam. size: 600 mm.	
5.3 Distance from stern to aft of last hold opening: 5.31 State deck strength: 4.5 mt/sqm Ballast 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.28		NO.1# 5.0 m , NO.2,3,4,5# 4.20 m	
5.31 State deck strength: 4.5 mt/sqm Ballast 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.29	Distance from bow to fore of 1 st hold opening:	18.40 m.	
Ballast 5.32 Capacity of ballast tanks (100%): 5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.3	Distance from stern to aft of last hold opening:	36.40 m.	
5.32 Capacity of ballast tanks (100%): 18,114.70 m3 5.33 Ballast holds capacity, state which hold(s): 13396.9 m3 (No. 3 Hold) 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.31	State deck strength:	4.5 mt/sqm	
5.33 Ballast holds capacity, state which hold(s): 5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	Ballast			
5.34 Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS	5.32	Capacity of ballast tanks (100%):	18,114.70 m3	
Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deballasting 1000 MT/HR. x2 SETS 5.35	5.33	Ballast holds capacity, state which hold(s):	13396.9 m3 (No. 3 Hold)	
5 00 L		Vessel's ballasting time / rate of ballasting / Vessel's deballasting time / rate of deball	asting 1000 MT/HR. x2 SETS	
5.36 Unpumpable quantity: 200 m3	5.36	Unpumpable quantity:	200 m3	

6	CARGO GEAR (ONLY TO BE COMPLETED IF AP	PLICABLE)			
6.1	.1 If geared state make and type:		IHI Electro Hydraulic	WM / H 360200-280B	
6.2	2 Number/location of derricks-/ cranes: 4		4 x cranes x 36MT, betwee	n 1&2, 2&3, 3&4, 4&5	
6.3	Maximum outreach of gear beyond ships rail		11.	8 m.	
6.4	Maximum outreach of gear beyond ships rail with ma	aximum cargo lift on hook:	11	.8 m	
6.5	If gantry cranes/horizontal slewing cranes - state mir to top of hatch coaming:	nimum clearance distance crane hook	N	I/A	
6.6	Time needed for full cycle with maximum cargo lift or	n hook:	75	sec	
6.7	Hoisting time of gear: (Load / Metres Minutes)	Hook Grab	20 r	n/min	
6.8	Luffing time of gear:		66	sec	
6.9	Slewing time of gear:		0.8 r	ev/min	
6.1	Is gear combinable for heavy lift?		N	NO	
6.11	Are winches electro-hydraulic?		Y	ES	
6.12	If vessel has grabs on board - state:		YES		
			Yes 4 Nos x 18.8MT 6.5-14 CBM, Tare Weight 8.95mt SMAG Electro-hyd, MZGL 14000-6B		
	Weight:		8.95 MT.		
	Lifting Capacity:		18.	.8MT	
		Power source of grabs:			
		Location of power source:			
6.13	Does vessel have enough power to run 4 cranes and pls state how many?	d 4 shore grabs (if applicable). If not	Υ	YES	
6.14	Is vessel fitted with sufficient lights at each hatch for night work?		Υ	ES	
6.15	Is vessel logs fitted?		N	NO	
	If yes, state number, type and height of stanchions/sockets, if on board:		N/A		
	16 Is vessel log racks fitted?		NO		
6.17	Timber Loadline (if applicable)	Deadweight	Draft	TPC	
	Summer:				
	Winter:				
	Winter North Atlantic:				
	Fresh water:				
	Tropical:				
	Tropical fresh water:				

7		
7.1	Capacity in direct stow of TEU/FEU basis empty tanks:	
	Capacity in direct stow of TEU/FEU basis full tanks:	
7.2	Are all containers within reach of vessel's gear?	

7.3	If no, state self sustained capacity:	
7.4	If vessel fitted with all permanent and loose fittings/lashing materials for above number of TEU/FEU?	
7.5	Is vessel fitted with recessed holes/shoes on tanktop and container shoes on weatherdeck- and hatch covers?	
7.6	Advise stack weights and number of tiers on/under deck per TEU:	
	Advise stack weights and number of tiers on/under deck per FEU:	
7.7	Has vessel a container spreader on board?	
7.8	Number and type of reefer plugs:	

8	ENGINE ROOM, SPEED AND CONSUMPTION				
8.1	Is vessel fitted with a shaft generator?	NO			
Engine Roo	m				
8.2	Engine make/model and type:		DU-SULZE	R 6RT-flex50	
8.3	BHP / RPM of main engine at MCR:	100%	9480kW	124RPM	
8.4	BHP / RPM of main engine at NCR (as % of MCR):	85%	8058kW	118RPM	
8.5	BHP / RPM of main engine at MCR:	EPL	5132kW	101RPM	
8.6	GENERATORS :		Wartsila 64	5W 4L20 x 3	
Fuel					
8.5	What type/viscosity of fuel is used for main propulsic		17 VLSFO (Sulphur< 0.5%) 217:2017 LSMGO (Sulphur <		
	Capacity (100%) of main engine bunker tanks (LSIFO + HSIFO; excluding unpumpables):		LSFO 1548 m3; LSMGO 695 m3		
8.6	6 What type/viscosity of fuel is used in the generating plant:		RMG 380CST ISO 8217:2017 VLSFO (Sulphur< 0.5%) + In ECA area, DMA ISO 8217:2017 LSMGO (Sulphur < 0.1%)		
	Capacity (100%) of aux engine(s) bunker tanks (LSN unpumpables):	MGO + HSMGO; excluding	INCLUDED I	N M/E TANKS	
Speed					
8.7	Ballast:	ABT	AS DED VESSE	EL DESCRIPTION	
	Laden:	ABT	AS FER VESSE	LE DESCRIPTION	
Consumption	ons				
8.8	Passage		Main	Aux	
	Ballast:	ABT			
	Laden:	ABT	AS PER VESSEL DESCRIPTION		
8.9	In Port				
	Working:				
	Idle:				
	Other (specify): Vsl burns extra IFO/MDO when grab	s are operating ABT			

9	MISCELLANEOUS			
Communications and Electronics				
9.1	Call sign:	HSRW		
9.2	Vessel's INMARSAT – C number:	456700583 / 456700586		
9.3	Vessel's telephone number:	+6628449509 / +881677102497		
9.4	Vessel's fax number:	N/A		
9.5	Vessel's email address:	warisanaree@speedmailplus.com		
9.6	Vessel's MMSI No. (Maritime Mobile Selective call Identity Code):	567105000		
9.7	Vessel's onboard electrical supply (V / Hz):	440/220V 60 Hz and accommodation supply is 220V 60Hz		
Constants/Fresh Water				
9.8	Constants excluding fresh water:	350 MT		
9.9	Daily freshwater consumption:	8 mt		
9.1	Fresh water capacity:	239.10 m3		
9.11	State daily production of evaporator:	Capacity of evaporators: 22 MT and daily production 8.0 MT/ Day		
9.12	Normal fresh water reserve:	239.10 m3		
Insurance				
9.13	P & I Club - Full style:	The Swedtsh Club		
9.14	P & I Club coverage:	AS PER P N I RULES		
9.15	Where is the owners hull and machinery placed:	The Swedtsh Club		
9.16	Hull & Machinery insured value:	AS PER VESSEL DESCRIPTION		

Vetting				
9.17	Is the vessel RIGHTSHIP approved:	YES		
9.18	Date/Place of last RIGHTSHIP Inspection:	26-MAY-2020 / ONAHAMA, JAPAN		
Port State C	Control			
9.19	Date and place of last Port State Control inspection:	25- NOV-2023 / GDANSK, POLAND		
9.2	Has the vessel been detained by Port State Control in the last 12 months?	No		
	Any outstanding deficiencies as reported by any Port State Control. If yes, provide details:	N/A		
9.21	Any Australian Maritime Safety Authority (AMSA) detentions or noted deficiencies. If so, please advise details and specify when/where these items were repaired.	No		

10	SUPPLEMENTARY INFORMATION FOR SPECIFIC COMMODITIES/TRADES	
10.1		
		D. I.I. oo

2008 (BalticExchange.com / Baltic99.com)